

"BIGGER & STRONGER"

Commercial & Industrial Solution Supports Your Business

AlphaESS is a world-leading energy storage solution and service provider covering the full power range.

 @AlphaEnergyStorageSystem  @AlphaESS  @alpha_ess  @AlphaESS  www.alphaess.com

Alpha ESS Co., Ltd.

Tel: +86 513 8060 6891
Email: info@alpha-ess.com
Website: www.alphaess.com
Add: No. 1086 Bihua Road, Tongzhou District,
Nantong City, Jiangsu Province, China

Alpha ESS International Pte. Ltd.

Tel: +65 6513 1125 / +65 6513 1126
Email: Singapore@alpha-ess.com
Add: 2 Corporation Road #01-06A Corporation
Place 618494 Singapore

Alpha ESS Australia Pty. Ltd.

Tel: +61 02 9000 7676
Email: techsupport@alphaess.au
Website: www.alphaess.au
Add: 8/15-21 Gibbes Street, Chatswood,
NSW 2067 Australia

Alpha ESS Europe GmbH

Tel: +49 6196 7863485
Email: europe@alpha-ess.de
Website: www.alphaess.de
Add: Horizon Tower 17.OG, Alfred-Herrhausen-Allee 3-5,
65760 Eschborn, Germany

Alpha ESS UK Ltd.

Tel: +44 330 043 2610
Email: info@alpha-ess.com
Add: Drake house, Long street, Dursley, GL11 4hh UK

Alpha ESS Italy S.r.l.

Tel: +39 339 462 4288
Email: info@alphaess.it
Add: Via Del Molinuzzo 83, 59100 Prato (PO), Italy

Alpha ESS USA, Inc.

Tel: +1 408 368 7828
Email: usa@alpha-ess.com
Add: Unit 5 2180 S Ivanhoe St, Denver, CO 80222 USA

Alpha ESS Korea Co., Ltd.

Email: info@alpha-ess.com
Add: 2F, 19-4, Nohyeong 11-gil, Jeju-si, Jeju-do,
Republic of Korea

Alpha ESS Benelux B.V.

Email: contact@alphaess.nl
Add: High Tech Campus 41, 5656AE Eindhoven, Netherlands

YOUR
SMART
ENERGY



STORION-H30/H50-G3

COMMERCIAL & INDUSTRIAL SERIES

POWER

30 / 50 kW Hybrid Inverter

CAPACITY

STORION-H30-G3

72.3 / 144.6 kWh

STORION-H50-G3

120.5 / 241 kWh



KEY FEATURES

- **All-in-One Design**
The cabinet contains batteries, PCS, DC/DC, STS and EMS, but only occupies a small area.
- **Optimal for Multi-Direction Roof**
PV Input: 4*MPPT with 8 Input
- **Multiple System Operation Monitoring**
Web- and app-based cloud application for C&I use
- **Max. 10 systems in on-grid parallel, 4 systems in off-grid parallel**
On- / Off- grid switching time ≤ 20 ms.


STORION-H30/H50-G3



System Function

- Backup
- Peak Shaving and Load Shifting
- Max 10 Systems in Parallel on Grid
- TOU (Time of Use) Mode

System Diagram



Model	STORION-H30-G3	STORION-H50-G3
System Technical Specification		
System Capacity	72.3 kWh	120.5 kWh
Standard Battery Rack	1*	
Warranty	5 Years Product Warranty, 10 Years Battery Warranty	
PV Side (DC)		
Max. input power	60 kW	75 kW
Start-up voltage	210 V	
MPPT Voltage Range	200 ~ 850 V	330 ~ 850 V
Number of MPPT	4	
Number of Strings per MPPT	2	
Max. Input Current	40 A / 40 A / 40 A / 40 A	
Max. Short-circuit Current	50 A / 50 A / 50 A / 50 A	
AC side (on-grid)		
Nominal Output Power	30 kW	50 kW
Max. Input Apparent Power	60 kVA	80 kVA
Nominal Grid Voltage	3L / N / PE , 220 V / 380 V; 230 V / 400 V; 240 V / 415 V	
Nominal Grid Frequency	50 / 60 Hz (± 5 Hz)	
Max. Output Current	45.5 A	75.8 A
Max.THDr of current	< 3%	
AC Power Factor	0.8 leading ... 0.8 lagging	
AC side (off-grid)		
Nominal Output Power	30 kW	50 kW
Max. Output Apparent Power	30 kVA	50 kVA
Nominal Outpu Voltage	3L / N / PE , 220 V / 380 V; 230 V / 400 V; 240 V / 415 V	
Nominal Grid Frequency	50 / 60 Hz (± 5 Hz)	
Max. Output Current	45.5 A	75.8 A
Max.THDr of voltage	< 3%	
Overload	150%, 10 s	
Efficiency		
Max. Efficiency & European Efficiency	97.8% & 97.2%	
Round-Trip Efficiency (RTE) DC ↔ AC	92%	
General Parameter		
Dimensions (W x D x H)	1,120 x 1,300 x 2,050 mm	
Battery Module Connection	3 in series	5 in series
Weight	1,700 kg (with 5*M77314-S)	
Corrosion Protection Class	C4	
Ingress Protection	IP55	
Noise Emission	≤ 65 dB @ 1m	
Operating Temperature Range	-30 °C ~ 50 °C(PCS > 45°C derating)	
Operating Humidity Range	0% ~ 90% (No Condensation)	
Max. operating Altitude	3,000 m / 9,842 ft (> 3,000 m derating)	
Fire-fighting System	Aerosol + Smoke / Temperature Detection	
Cooling Method	HVAC	
Communication	RS485, CAN, Ethernet, Modbus TCP	
Dispatching Protocol	Modbus TCP, API	
Compliance	IEC 61000-1/-2/-3/-4, IEC 62109, IEC 62477,EN 50549, VDE 4105,VDE 4110, AS4777, NRS 097, NC RFG,G99/G100	

* Max support 2 battery racks, extra battery cabinet is needed.

STORION-H30/H50-G3



Model																			
Battery Module																			
Parameter																			
Model																			
M77314-S 0.5C																			
Battery Chemistry	LiFePO4																		
Pack Configuration	3.2 V / 314 Ah @ 1P24S																		
Internal Resistance	≤ 10 mΩ																		
Nominal Capacity	24.1 kWh																		
Nominal Voltage	76.8 V																		
Operating Voltage Range	69.6 V ~ 84 V																		
Max. Charging/Discharging Current	157 A																		
Cycle Life	8,000@EOL 70% **																		
Operating Ambient Temperature Range	-20 °C ~ 50 °C***																		
Ingress Protection	IP 20																		
Communication	CAN																		
Dimensions (W x D x H)	526 x 814 x 250 mm																		
Weight	168 kg																		
Compliance	IEC 61000-1/-2/-3/-4, IEC 62619, IEC 62109, UL9540A																		
Meter (optional)																			
	<table><tr><th>Model</th><th>DTSU666</th></tr><tr><td>Rated Voltage</td><td>230 V AC / 400 V AC</td></tr><tr><td>Accuracy Class</td><td>± 1%</td></tr><tr><td>Communication</td><td>RS485, Modbus RTU</td></tr><tr><td>Dimensions (W x D x H)</td><td>42 x 66 x 81.5 mm</td></tr><tr><td>CT Model</td><td>AKH-0.66</td></tr><tr><td>CT Current Ratio</td><td>400 / 5 A</td></tr><tr><td>CT Perforation Size</td><td>Φ 36 mm</td></tr></table>	Model	DTSU666	Rated Voltage	230 V AC / 400 V AC	Accuracy Class	± 1%	Communication	RS485, Modbus RTU	Dimensions (W x D x H)	42 x 66 x 81.5 mm	CT Model	AKH-0.66	CT Current Ratio	400 / 5 A	CT Perforation Size	Φ 36 mm		
Model	DTSU666																		
Rated Voltage	230 V AC / 400 V AC																		
Accuracy Class	± 1%																		
Communication	RS485, Modbus RTU																		
Dimensions (W x D x H)	42 x 66 x 81.5 mm																		
CT Model	AKH-0.66																		
CT Current Ratio	400 / 5 A																		
CT Perforation Size	Φ 36 mm																		
Extension Battery Cabinet (optional)																			
	<table><tr><th>Model</th><th>Extension Battery Cabinet</th></tr><tr><td>Battery</td><td>M77314 - S</td></tr><tr><td>Rack Capacity</td><td>72.3 kWh / 120.5 kWh</td></tr><tr><td>Max. Charging / Discharging Current</td><td>157 A</td></tr><tr><td>Battery Rack Voltage Range</td><td>208.8 ~ 252 V / 348 ~ 420 V</td></tr><tr><td>Number of Battery Module</td><td>3 / 5 in series</td></tr><tr><td>Fire-fighting System</td><td>Aerosol + Smoke / Temperatur Detection</td></tr><tr><td>Dimensions (W x D x H)</td><td>1,120 x 1,300 x 2,050 mm</td></tr><tr><td>Weight</td><td>1,600 kg (with 5 * M77314 - S)</td></tr></table>	Model	Extension Battery Cabinet	Battery	M77314 - S	Rack Capacity	72.3 kWh / 120.5 kWh	Max. Charging / Discharging Current	157 A	Battery Rack Voltage Range	208.8 ~ 252 V / 348 ~ 420 V	Number of Battery Module	3 / 5 in series	Fire-fighting System	Aerosol + Smoke / Temperatur Detection	Dimensions (W x D x H)	1,120 x 1,300 x 2,050 mm	Weight	1,600 kg (with 5 * M77314 - S)
Model	Extension Battery Cabinet																		
Battery	M77314 - S																		
Rack Capacity	72.3 kWh / 120.5 kWh																		
Max. Charging / Discharging Current	157 A																		
Battery Rack Voltage Range	208.8 ~ 252 V / 348 ~ 420 V																		
Number of Battery Module	3 / 5 in series																		
Fire-fighting System	Aerosol + Smoke / Temperatur Detection																		
Dimensions (W x D x H)	1,120 x 1,300 x 2,050 mm																		
Weight	1,600 kg (with 5 * M77314 - S)																		
Parallel Backup Box(Optional)																			
	<table><tr><th>Model</th><th>Parallel Backup Box</th></tr><tr><td>Max. Connection systems</td><td>4</td></tr><tr><td>Nominal Power</td><td>200 kW</td></tr><tr><td>Nominal Frequency</td><td>50/60 Hz</td></tr><tr><td>Switching Time</td><td>≤ 20 ms</td></tr><tr><td>Ingress Protection</td><td>IP54</td></tr><tr><td>Operating Ambient Temperature Range</td><td>-25 °C ~ 50 °C</td></tr><tr><td>Dimensions (W x D x H)</td><td>600 × 255 × 800 mm</td></tr><tr><td>Weight</td><td>40 kg</td></tr></table>	Model	Parallel Backup Box	Max. Connection systems	4	Nominal Power	200 kW	Nominal Frequency	50/60 Hz	Switching Time	≤ 20 ms	Ingress Protection	IP54	Operating Ambient Temperature Range	-25 °C ~ 50 °C	Dimensions (W x D x H)	600 × 255 × 800 mm	Weight	40 kg
Model	Parallel Backup Box																		
Max. Connection systems	4																		
Nominal Power	200 kW																		
Nominal Frequency	50/60 Hz																		
Switching Time	≤ 20 ms																		
Ingress Protection	IP54																		
Operating Ambient Temperature Range	-25 °C ~ 50 °C																		
Dimensions (W x D x H)	600 × 255 × 800 mm																		
Weight	40 kg																		

** Under specific test conditions.

*** Max. charge / discharge current derating may occur with changes in temperature and SoC.

